




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61G 11/00	A1	(11) International Publication Number: WO 99/21526 (43) International Publication Date: 6 May 1999 (06.05.99)
(21) International Application Number: PCT/NO98/00320 (22) International Filing Date: 28 October 1998 (28.10.98) (30) Priority Data: 974982 29 October 1997 (29.10.97) NO (71)(72) Applicant and Inventor: HAMSUND, Torgeir [NO/NO]; Lybekkveien 48a, N-0385 Oslo (NO). (74) Agent: BALLE, Morten; Protector Intellectual Property Con- sultants A/S, P.O. Box 5074, Majorstua, N-0301 Oslo (NO).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i> <i>In English translation (filed in Norwegian).</i>

(54) Title: INFANT INCUBATOR**(57) Abstract**

An incubator for premature or weakly infants comprising a base section (9, 15) which serves as a support for both the infant in the incubator and a protective top section (1, 2) which is made of a substantially transparent material, wherein the base section (9, 15) houses means for the circulation of air (13) to the chamber (23) enclosed by the base section (9, 15) and the top section (1, 2), and means (14, 17) for adjusting the temperature, composition and humidity of the air, and also ducts (7, 12, 8, 11) for the supply of air to the chamber (23) and the outlet of air from the chamber (23) respectively, and wherein the top section consists of an outer shell (1) and an inner shell (2), which shells (1, 2) rest on the base section (9, 15) and wherein the inner shell (2) is open at the top, and wherein the portholes (20) preferably equipped with covers (22), are provided in the top section (1, 2), wherein the ducts (7) for the supply of air to the incubator open into the chamber (23) against and on the inside of the inner shell (2) and the air outlet ducts (8) run out between the inner (2) and the outer (1) shell.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INFANT INCUBATOR

The present invention relates to an improved infant incubator.

- 5 The purpose of an infant incubator is to secure and improve the chances of survival of a premature or weakly infant. This is accomplished by keeping the infant in an environment which is warm, moist and contains sufficient oxygen. A premature infant has a low body weight, and thus a body temperature which is close to the ambient temperature. The premature infant is therefore very vulnerable to temperature swings,
10 and consequently major efforts have been made to develop incubators which maintain as constant a temperature as possible.

- The incubators dominating today's market comprise a lower section housing equipment for adjusting the temperature and the composition of the gas delivered to the premature
15 infant. Placed on this lower section is an upper section made of a transparent material, through which there are provided closable portholes to allow the premature infant to be cared for without removing the whole of the upper section. Inside the incubator, the infant lies on a mattress which forms the dividing line between the upper and the lower section. The gas in the incubator comprising air, possibly with the addition of extra
20 oxygen and moisture, circulates up between the walls of the incubator and the mattress on one side, and down into a corresponding opening on the opposite side of the incubator. To improve the flow pattern of the gas, an inner wall is often provided in the upper section of the incubator, causing the gas to flow up and down between the outer shell and the inner wall in the upper section of the incubator. Means for heating,
25 humidifying and circulating the air flow are provided in the lower section of the incubator. This means that a heating element and a fan are located in proximity to the premature infant. The heating element and fan may be the source of some electromagnetic radiation, a radiation which at present is the subject of intense discussion with respect to whether it has any effects on health. In addition, and more
30 importantly, a fan of this kind cannot be entirely noise-free and is thus the source of an acoustic nuisance for the tiny patient.

- Moreover, when a porthole is opened in the upper section, the circulating air will draw the colder air of the surroundings with it into the incubator, which may cause the
35 temperature in such an incubator to fall by about 2°C when a door is open for more than 10 minutes. A temperature drop of this kind may at first seem to be insignificant, but is most unfortunate for the extraordinarily vulnerable premature infant who has little

energy to burn and low heat capacity. The doors must be opened from time to time to care for and carry out test procedures on the premature infant. Moreover, it is desirable that the premature infant should not be completely isolated from the surroundings since, just as other infants, the premature infant needs body contact - even if nothing more
5 than the touch of a friendly hand. The portholes in the incubator may therefore remain open for many periods of more than 10 minutes.

The object of the present invention is to provide an infant incubator where the aforementioned problems are obviated.

10

This is achieved according to the present invention by means of an incubator for a prematurely born or weakly infant comprising a base section which serves as a support for both the infant placed in the incubator and a protective top section or hood which is made of a substantially transparent material, wherein the base section houses means for
15 causing air to circulate to the chamber enclosed by the base section and the top section, and means for adjusting the temperature, composition and humidity of the air, and ducts for the supply of air to the chamber and the outlet of air from the chamber respectively, and wherein the top section consists of an outer shell and an inner shell, which shells rest on the base section and wherein the inner shell is open at the top, and wherein
20 portholes, preferably equipped with covers, are provided in the top section, wherein the incubator air supply ducts open into the chamber against and on the inside of the inner shell and the air outlet ducts run out between the inner and the outer shell.

In the present infant incubator, the air flows in on the inside of the inner shell in contrast
25 to the previously known incubators. This ensures that the air circulates through the chamber in which the weakly neonate is lying and provides a constant adequate supply of oxygen-rich air to the infant.

Whilst in the incubator, the infant must be cared for, tests must often be taken and the
30 infant also needs physical contact. In the present incubator, the problem of the incoming air drawing with it "cold" outside air into the chamber of the incubator is reduced or prevented.

The present invention will now be explained with the aid of the attached figures,
35 wherein:

Figure 1 is a sectional view through a preferred embodiment of the present infant incubator;

Figure 2 is a similar sectional view through the present incubator, but where a porthole is open;

5 Figure 3 is a sectional view through an alternative embodiment of the present incubator; and

Figure 4 is a longitudinal section through a conventional incubator.

10 Figures 1, 2 and 3 show two preferred embodiments of the incubator, whilst Figure 4 is a sectional view through a conventional incubator which is surrounded by an outer shell a and wherein an inner shell b is provided in parts of the incubator. A fan f in a lower chamber g causes the air to circulate up between the inner and the outer shell on one side and down between the inner and the outer shell on the other side. Attending personnel and parents can gain access to the infant in the incubator through portholes
15 covered by cover c.

The present incubator, in the simplest, and preferred embodiment as shown in Figures 1 and 2, comprises a top section 1, 2 and a base section 9, 15. The top section 1, 2 comprises an outer hemispherical shield 1 in a transparent material and an inner
20 hemispherical shell 2 cut open at the top, between which shells there is an air space. The outer shell 1 and inner shell 2 rest on respective seats 5, 6 on the base section 9, 15. The infant lies inside a chamber 23 defined by the top section 1, 2 and the base section 9, 15, and preferably lies on a bottom board 10 which either is soft in itself or on which a mattress is provided.

25 The portholes 20 in the top section 1, 2 allowing the infant to be cared for pass through both the outer shell 1 and the inner shell 2 and are connected by a collar 21. Additionally, the portholes 20 are normally closed by covers 22. The collar 21 fits closely against the portholes 20 in the outer 1 and the inner 2 shell respectively.

30 Air is supplied to the chamber 23 through air supply pipe 11 and duct 8 in the base section 9, 15, and flows out into the chamber 23 from the ducts 8 between the base section 9 and the bottom board 10, up along the edges of the bottom board 10 and on the inside of the inner shell 2. This thus ensures a constant adequate flow of fresh air to the
35 infant lying in the incubator with a minimum through-flow of air. Moreover, the bottom board 10 and the mattress, if any, will be heated from below by the air flowing into the incubator.

When the incubator covers 22 are closed, the air flows up on the inside of the inner shell 2 and up into the top of the top section 1, 2 and is drawn out again through the space between the outer 1 and the inner 2 shell and down into an outlet duct 7 and then to the
5 air outlet pipe 12 in the base section 9, 15.

When one or more of the covers 22 are opened, the incubator is opened to its surroundings and air can flow into the chamber 23 through the portholes 20. The very fact that the air flow closest to the infant, that is, the air on the inside of the inner shell 2,
10 is rising, largely prevents the air closest to the infant from being mixed with cold and possibly contaminated air. The air entering the portholes 20 is conducted upwards and away from the infant and out between the outer 1 and the inner 2 shell.

To further ensure that the air flowing downwards between the shells 1, 2 does not flow
15 into the chamber 23 through the portholes in the inner shell 2, a collar 21 is preferably provided which tightly connects the inner 2 and the outer 1 shell.

As shown in the figures, the base section is preferably divided into a supporting member 9 and a bottom member 15, wherein the bottom member 15, which may optionally be
20 mounted on non-illustrated wheels, contains the equipment necessary for maintaining a flow of air which in turn maintains the desired environment in the incubator. In the illustrated embodiment, this equipment comprises a fan 13 for the circulation of air, and also means 14 for heating and humidifying the air. A supply duct 18 for the supply of fresh, optionally oxygen-enriched, air to the incubator is also preferably provided in
25 connection with the bottom member. The supply duct 18 will supply air to replace any air which might leak out because the incubator is not completely airtight and also replace oxygen which is used by the infant in the incubator.

The supply duct 18 in the illustrated embodiment is connected to the air outlet pipe 12
30 counterflow of the fan 13. The air entering through the supply duct 18 is thus heated and humidity is introduced therein before it is passed into the chamber 23. The air entering the supply duct 18 is preferably filtered, in addition to the composition of the air being adjustable, before it is fed into the incubator.

35 A valve 19 is fitted at the point where the supply duct 18 enters the air outlet pipe 12. The valve 19 functions as a three-way valve which is adapted for respectively admitting

and blocking the air flow through the air outlet pipe 12, whilst respectively closing and opening the supply duct 18.

It is preferable that the valve 19 should close the air outlet pipe 12 and open the supply duct 18 when one or more of the covers 22 are to be opened. The attending personnel can do this manually by manoeuvring the valve 19 into the desired position before the door is opened and back again after the door has been closed. It is most preferable that the valve 19 should be manoeuvred in response to the opening of one or more of the covers 22, for example, by means of a micro-switch in connection with the doors 22, or with the aid of sensors which trigger the manoeuvring of the valve 19, for example, owing to a change in pressure in the chamber 23. The incubator thus becomes a plenum chamber with a small overpressure in the chamber 23 relative to the surroundings, and this ensures that cold and possibly impure air is not drawn into the incubator through open portholes 20.

The bottom member 15 which contains the means for circulating, adjusting the composition of and heating the air which is to be circulated in the incubator chamber is preferably located close to or on the floor at a distance from the chamber 23 in which the infant is to lie. The bottom member 15 houses a fan 13 as well as means 14 for heating and humidifying the circulating air flow, thus reducing considerably the acoustic nuisance and also any electromagnetic radiation in the chamber 23. The fan 13 which causes circulation of the air can never be noiseless, and for this reason sound absorbers 16, may be provided, e.g., in the air supply pipe 11 and/or in an equalising chamber 17 in the base unit. The purpose of the equalising chamber 17, besides the fact that the sound absorbers 16 may be placed there, is to ensure that all the circulating air is mixed and is as homogeneous as possible.

It may be preferable that the bottom member 15 be mounted on wheels, enabling the unit to be moved easily. The bottom member 15 and the supporting member 9 are connected to the air supply pipe 11 and the air outlet pipe 12 which are connected to inlet duct 8 and outlet duct 7 respectively in the supporting member 9.

The air supply pipe 11 and the air outlet pipe 12 may be telescopic, enabling the height of the supporting member 9 above the floor to be adjusted according to need. The pipes 11, 12 alone may form the only connection between the bottom member 15 and the supporting member 9, thereby providing the necessary rigidity, but it is preferable that

the members 9, 15 should be connected by a non-illustrated supporting column which provides the necessary rigidity and adjustment facility.

Whilst an infant is in the incubator, it may be preferable that the infant be placed with a part of the body, such as the head, either higher or lower than the rest of the body. In conventional incubators, this is done by building up under the mattress at the one end. This in turn will give a larger space between the mattress and the walls of the incubator which means that articles may easily be lost under the mattress.

10 However, in the case of the present incubator, this problem can be solved by inserting a swivel in the pipes 11 and 12 and optionally also on the aforementioned, but non-illustrated supporting column. This swivel, which must be lockable at any angle of choice, is preferably located as high as possible in the pipes 11, 12 and the optional supporting column, and so as close to the supporting member 9 as possible. For
15 example, the swivel may coincide with the junction between the pipes 11, 12 and the supporting member 9.

The bottom board 10 may be fixedly mounted on the supporting member 9. However, it is preferred that the bottom board 10 be capable of rotation to facilitate access to and
20 care of the infant in the incubator, without having to open more portholes than absolutely necessary and without having to lift the infant unnecessarily. This possibility of rotating the bottom board 10, and thus the infant, is of great importance for best possible access to the infant during routine nursing and care. Normally, in its simple form, the incubator will have a bottom board 10 which can be rotated manually by the
25 attending person inserting his hands into the openings and turning the bottom board 10 with his hands. If so desired, the incubator may be equipped with a locking device which prevents the bottom board from turning unintentionally, or with a motor or the like for rotating the bottom board 10 without having to open the incubator.

30 Figure 3 shows an alternative embodiment of the present incubator. This embodiment is preferred in cases where it is desirable that the incubator for periods of time should be capable of being used without the dome-shaped outer shell 1. In principle, this incubator is like that illustrated in Figures 1 and 2, and when closed, i.e., when the outer shell is mounted, will be identical thereto in terms of function. The difference between
35 the embodiment shown in Figures 1 and 2 and that shown in Figure 3 is that the lowermost part of the inner shell 2 has been cut off and replaced with a ring 24 which is located on the supporting member 9 and which protects the infant against draughts from

the side. When the incubator is closed, the ring 24 seals against the lower edge of the inner shell 2.

Figure 3 also shows the flow pattern of the air flow in the open incubator. Certain
5 hospitals prefer to use open incubators of this kind. However, the open incubator has its limitations which are overcome by this combination of open incubator which can readily be converted into a closed incubator.

The present incubator is shown with a preferred dome-shaped outer shell 1. A dome-
10 shaped outer shell 1 means that there are no flat surfaces on which foreign bodies may be placed. Foreign bodies of various kinds will inevitably be placed on an incubator with a flat top, even though the instructions state that this must not be done. Foreign bodies, such as items of equipment belonging to doctors and nurses, must not be placed
15 on the incubator top as this creates noise for the infant in the incubator, both when the items are put there and when they remain there and vibrate on the top. It will be difficult or impossible to use the top of the incubator as a storage space when the shell is dome-shaped.

The infant lying in the incubator will be disturbed by light. In a neonatal care unit with
20 a plurality of incubators, there will be activity around the clock and it will be relatively light. This will prevent the infant from having the sleep he needs. The present incubator can therefore be equipped with an outer shell 1 of a material which allows control of light penetration. Such materials are known and are used *inter alia* in windows having adjustable light penetration and in welding goggles where light
25 penetration can be adjusted electronically.

The invention has been described for an incubator consisting of a bottom member 15 for each unit. However, it is also conceivable that a bottom member 15 may be connected
30 to two or more incubator units comprising the supporting member 9, bottom board 10 and the top section 1, 2.

Patent claims

1.

An incubator for premature or weakly infants comprising a base section (9, 15) which
5 serves as a support for both the infant in the incubator and a protective top section (1, 2)
which is made of a substantially transparent material,
wherein the base section (9, 15) houses means for the circulation of air (13) to the
chamber (23) enclosed by the base section (9, 15) and the top section (1, 2), and means
(14, 17) for adjusting the temperature, composition and humidity of the air, and also
10 ducts (7, 12, 8, 11) for the supply of air to the chamber (23) and the outlet of air from
the chamber (23) respectively, and wherein the top section consists of an outer shell (1)
and an inner shell (2), which shells (1, 2) rest on the base section (9, 15) and wherein the
inner shell (2) is open at the top, and wherein portholes (20), preferably equipped with
covers (22), are provided in the top section (1, 2), characterised in that the ducts (7) for
15 the supply of air to the incubator open into the chamber (23) against and on the inside of
the inner shell (2) and the ducts (8) for the outlet of air run out between the inner (2) and
the outer (1) shell.

2.

20 An incubator according to claim 1, characterised in that the portholes (20) pass through
both the inner and the outer shell (1, 2) and that the shells (1, 2) are connected in the
portholes (20).

3.

25 An incubator according to claim 2, characterised in that the shells in the portholes (20)
are connected by means of collars (21) which are closely fitted in the portholes in the
inner and the outer shell (1, 2) respectively.

4.

30 An incubator according to any of the preceding claims, characterised in that in the air
outlet ducts (8, 11) there are provided means (19) which allow the temporary closure of
the outlet ducts (8, 11) and at the same time temporary admission of the supply of air
from a supply duct (18).

35 5.

An incubator according to claim 4, characterised in that the means (19) for closure of
the outlet ducts (8, 11) and admission of the supply of air from the supply duct (18) are

arranged to close the outlet ducts (8, 11) and admit the supply of air from supply duct (18) when one or more of the covers (22) are opened.

6.

- 5 An incubator according to any one of the claims, characterised in that the base section is divided into two, an air treatment unit (15) containing the means (13) for the circulation of air and the means (14, 17) for adjusting the temperature, composition and humidity of the air, and a supporting member (9) which forms a base for the top covers (1, 2), wherein the air treatment unit and the supporting member (9) are connected to one
10 another via pipes or tubes (11, 12).




Fig.1




Fig.2





FIG. 3




Fig. 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 98/00320

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A61G 11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A61G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0236851 A2 (DRÄGERWERK AKTIENGESELLSCHAFT), 16 Sept 1987 (16.09.87) --	1-6
A	EP 0687458 A1 (OHMEDA INC.), 20 December 1995 (20.12.95) --	1-6
A	EP 0447958 A1 (DRÄGERWERK AKTIENGESELLSCHAFT), 25 Sept 1991 (25.09.91) -- -----	1-6

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document but published on or after the international filing date	"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

6 April 1999

Date of mailing of the international search report

07-04-1999

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Ingrid Falk

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/03/99

International application No.

PCT/NO 98/00320

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0236851 A2	16/09/87	DE 3607575 A US 4846783 A	10/09/87 11/07/89
EP 0687458 A1	20/12/95	CA 2148212 A JP 8000679 A US 5539854 A	16/12/95 09/01/96 23/07/96
EP 0447958 A1	25/09/91	DE 4008822 A DE 69103302 D,T ES 2062584 T US 5100375 A	26/09/91 14/06/95 16/12/94 31/03/92